# Author Index


| | | |
|---|---|---|
| Bartlett, H. | Hybrid modelling, simulation and torque control of a marine propulsion system | 1–10 |
| Belgharbi, M. | Control of an electropneumatic actuator: comparison between some linear and non-linear control laws | 387–406 |
| Berg, H. | Design and testing of a robust linear controller for secondary controlled hydraulic drive | 375–386 |
| Best, M. C. | A randomized integral error criterion for parametric identification of dynamic models of mechanical systems | 119–134 |
| Brun, X. | Control of an electropneumatic actuator: comparison between some linear and non-linear control laws | 387–406 |
| Brunn, P. | A hybrid artificial neural network inverse kinematic solution for accurate robot path control | 23–32 |
| Burton, R. T. | Neural networks and hydraulic control—from simple to complex applications | 349–358 |
| Cai, L. | Robust friction compensation for precise and smooth position regulation | 157–161 |
| Caliskan, F. | Sensor fault detection in flight control systems based on the Kalman filter innovation sequence | 243–248 |
| Cao, Y.-Y. | Robust control for uncertain discrete-time jump linear systems with time delay | 477–488 |
| Cetinkunt, S. | Hydraulic actuator control with open-centre electrohydraulic valve using a cerebellar model articulation controller neural network algorithm | 33–48 |
| Chen, J. | Non-linear dynamic systems fault detection and isolation using fuzzy observers | 467–476 |
| Choi, C. | Attenuation of previewable/unmeasureable disturbances acting on dynamic plants | 135–144 |
| Cobo, M. | Hydraulic actuator control with open-centre electrohydraulic valve using a cerebellar model articulation controller neural network algorithm | 33–48 |
| Dimov, S. S. | Intelligent product manuals | 65–76 |
| Ebrahimi, M. | Mechanical drive control | 301–310 |
| Ebrahimi, M. | Multivariable system regulation with minimum control effort | 505–514 |
| Fairlie-Clarke, A. C. | Force as a flow variable | 77–81 |
| Farid, M. | On the optimal control of flexible manipulators | 267–273 |
| Fotouhi-C, R. | Parameter identification and trajectory following of a two-link rigid manipulator | 455–466 |
| Frank, P. M. | Robust control for uncertain discrete-time jump linear systems with time delay | 477–488 |
| Freebody, N. | A time-encoded signal-processing approach to fault classification of an electrohydraulic pressure control system and its application to a hot steel strip rolling mill | 407–426 |
| Fung, Y. H. | Performance improvement of robot manipulator control using an on-line neural network compensator | 49–60 |
| Gale, K. W. | A real-time expert system for the condition monitoring of hydraulic control systems in a hot steel strip finishing mill | 359–374 |
| Gawthrop, P. J. | Thermal modelling using mixed energy and pseudo bond graphs | 201–216 |
| Gomma, H. W. | Robust control of a 1.5 MW free turbine engine | 217–228 |
| Gordon, T. J. | A randomized integral error criterion for parametric identification of dynamic models of mechanical systems | 119–134 |
| Gupta, M. M. | Parameter identification and trajectory following of a two-link rigid manipulator | 455–466 |
| Hajiyev, C. M. | Sensor fault detection in flight control systems based on the Kalman filter innovation sequence | 243–248 |
| Halikias, G. D. | Modelling and $H^{\infty}$ control of a single-link flexible manipulator | 85–104 |
| Harris, C. J. | An intelligent guidance and control system for ship obstacle avoidance | 311–320 |
| Helduser, S. | Electric–hydrostatic drive—an innovative energy-saving power and motion control system | 427–437 |
| Héraud, N. | Sensor network design for processes described by linear–bilinear equations | 321–329 |
| Hong, G. S. | A methodology to reduce large overshoot in a direct neural control system | 449–453 |
| Hong, X. | An intelligent guidance and control system for ship obstacle avoidance | 311–320 |
| Hwang, T. | Hydraulic actuator control with open-centre electrohydraulic valve using a cerebellar model articulation controller neural network algorithm | 33–48 |
| Ingram, R. | Hydraulic actuator control with open-centre electrohydraulic valve using a cerebellar model articulation controller neural network algorithm | 33–48 |
| Ivantysynova, M. | Design and testing of a robust linear controller for secondary controlled hydraulic drive | 375–386 |
| Khalid, M. | Adaptive general regression neural network for modelling of dynamic plants | 275–287 |




© IMechE 1999

# Author Index


| | | |
|---|---|---|
| Bartlett, H. | Hybrid modelling, simulation and torque control of a marine propulsion system | 1–10 |
| Belgharbi, M. | Control of an electropneumatic actuator: comparison between some linear and non-linear control laws | 387–406 |
| Berg, H. | Design and testing of a robust linear controller for secondary controlled hydraulic drive | 375–386 |
| Best, M. C. | A randomized integral error criterion for parametric identification of dynamic models of mechanical systems | 119–134 |
| Brun, X. | Control of an electropneumatic actuator: comparison between some linear and non-linear control laws | 387–406 |
| Brunn, P. | A hybrid artificial neural network inverse kinematic solution for accurate robot path control | 23–32 |
| Burton, R. T. | Neural networks and hydraulic control—from simple to complex applications | 349–358 |
| Cai, L. | Robust friction compensation for precise and smooth position regulation | 157–161 |
| Caliskan, F. | Sensor fault detection in flight control systems based on the Kalman filter innovation sequence | 243–248 |
| Cao, Y.-Y. | Robust control for uncertain discrete-time jump linear systems with time delay | 477–488 |
| Cetinkunt, S. | Hydraulic actuator control with open-centre electrohydraulic valve using a cerebellar model articulation controller neural network algorithm | 33–48 |
| Chen, J. | Non-linear dynamic systems fault detection and isolation using fuzzy observers | 467–476 |
| Choi, C. | Attenuation of previewable/unmeasureable disturbances acting on dynamic plants | 135–144 |
| Cobo, M. | Hydraulic actuator control with open-centre electrohydraulic valve using a cerebellar model articulation controller neural network algorithm | 33–48 |
| Dimov, S. S. | Intelligent product manuals | 65–76 |
| Ebrahimi, M. | Mechanical drive control | 301–310 |
| Ebrahimi, M. | Multivariable system regulation with minimum control effort | 505–514 |
| Fairlie-Clarke, A. C. | Force as a flow variable | 77–81 |
| Farid, M. | On the optimal control of flexible manipulators | 267–273 |
| Fotouhi-C, R. | Parameter identification and trajectory following of a two-link rigid manipulator | 455–466 |
| Frank, P. M. | Robust control for uncertain discrete-time jump linear systems with time delay | 477–488 |
| Freebody, N. | A time-encoded signal-processing approach to fault classification of an electrohydraulic pressure control system and its application to a hot steel strip rolling mill | 407–426 |
| Fung, Y. H. | Performance improvement of robot manipulator control using an on-line neural network compensator | 49–60 |
| Gale, K. W. | A real-time expert system for the condition monitoring of hydraulic control systems in a hot steel strip finishing mill | 359–374 |
| Gawthrop, P. J. | Thermal modelling using mixed energy and pseudo bond graphs | 201–216 |
| Gomma, H. W. | Robust control of a 1.5 MW free turbine engine | 217–228 |
| Gordon, T. J. | A randomized integral error criterion for parametric identification of dynamic models of mechanical systems | 119–134 |
| Gupta, M. M. | Parameter identification and trajectory following of a two-link rigid manipulator | 455–466 |
| Hajiyev, C. M. | Sensor fault detection in flight control systems based on the Kalman filter innovation sequence | 243–248 |
| Halikias, G. D. | Modelling and $H^{\infty}$ control of a single-link flexible manipulator | 85–104 |
| Harris, C. J. | An intelligent guidance and control system for ship obstacle avoidance | 311–320 |
| Helduser, S. | Electric–hydrostatic drive—an innovative energy-saving power and motion control system | 427–437 |
| Héraud, N. | Sensor network design for processes described by linear–bilinear equations | 321–329 |
| Hong, G. S. | A methodology to reduce large overshoot in a direct neural control system | 449–453 |
| Hong, X. | An intelligent guidance and control system for ship obstacle avoidance | 311–320 |
| Hwang, T. | Hydraulic actuator control with open-centre electrohydraulic valve using a cerebellar model articulation controller neural network algorithm | 33–48 |
| Ingram, R. | Hydraulic actuator control with open-centre electrohydraulic valve using a cerebellar model articulation controller neural network algorithm | 33–48 |
| Ivantysynova, M. | Design and testing of a robust linear controller for secondary controlled hydraulic drive | 375–386 |
| Khalid, M. | Adaptive general regression neural network for modelling of dynamic plants | 275–287 |




© IMechE 1999

| | | |
|---|---|---|
| Kim, J. S. | Attenuation of previewable/unmeasureable disturbances acting on dynamic plants | 135–144 |
| Ko, J. M. | Modelling and identification of a wire-cable vibration isolator via a cyclic loading test. Part 2: identification and response prediction | 173–182 |
| Ko, J. M. | Modelling and identification of a wire-cable vibration isolator via a cyclic loading test. Part 1: experiments and model development | 163–171 |
| Koehler, D. | Hydraulic actuator control with open-centre electrohydraulic valve using a cerebellar model articulation controller neural network algorithm | 33–48 |
| Kremer, G. G. | Parametric model development and quantitative feedback design for automotive torque converter bypass clutch control | 249–266 |
| Lin, N. L. | Performance improvement of robot manipulator control using an on-line neural network compensator | 49–60 |
| Linjama, M. | Low-order dynamic model for flexible hydraulic cranes | 11–22 |
| Lopez-Toribio, C. J. | Non-linear dynamic systems fault detection and isolation using fuzzy observers | 467–476 |
| Lou, Y. F. | A hybrid artificial neural network inverse kinematic solution for accurate robot path control | 23–32 |
| Lucas, T. N. | A note on order reduction by the discrete-time least-squares Padé method | 61–64 |
| Luh, G.-C. | Non-linear system identification using genetic algorithms | 105–118 |
| Lukasiewicz, S. A. | On the optimal control of flexible maniplators | 267–273 |
| Martin, K. F. | Diagnostics of a coolant system via neural networks | 229–241 |
| Marzi, M. H. | Diagnostics of a coolant system via neural networks | 229–441 |
| Mazzour, E. H. | Sensor network design for processes described by linear–bilinear equations | 321–329 |
| Mitchell, D. | Mechanical drive control | 301–310 |
| Murrenhoff, H. | Systematic approach to the control of hydrostatic drives | 333–347 |
| Ni, Y. Q. | Modelling and identification of a wire-cable vibration isolator via a cyclic loading test. Part 1: experiments and model development | 163–171 |
| Ni, Y. Q. | Modelling and identification of a wire-cable vibration isolator via a cyclic loading test. Part 2: identification and resposne prediction | 173–182 |
| Nikiforuk, P. N. | Neural networks and hydraulic control—from simple to complex applications | 349–358 |
| Nikiforuk, P. N. | Parameter identification and trajectory following of a two-link rigid manipulator | 455–466 |
| Ohnishi, H. | Frequency-shaped sliding mode control of an electrohydraulic servo-motor | 441–448 |
| Ottman, R. | Hydraulic actuator control with open-centre electrohydraulic valve using a cerebellar model articulation controller neural network algorithm | 33–48 |
| Owens, D. H. | Robust control of a 1.5 MW free turbine engine | 217–228 |
| Patton, R. J. | Non-linear dynamic systems fault detection and isolation using fuzzy observers | 467–476 |
| Pham, D. T. | Intelligent product manuals | 65–76 |
| Pinsopon, U. | Hydraulic actuator control with open-centre electrohydraulic valve using a cerebellar model articulation controller neural network algorithm | 33–48 |
| Plummer, A. R. | Modelling and $H^{\infty}$ control of a single-link flexible manipulator | 85–104 |
| Poo, A. N. | A methodology to reduce large overshoot in a direct neural control system | 449–453 |
| Rizvi, S. S. I. | Hybrid modelling, simulation and torque control of a marine propulsion system | 1–10 |
| Rossiter, D. | Robust control of a 1.5 MW free turbine engine | 217–228 |
| Sadri, A. M. | Robust strategies for active vibration control of plate-like structures: theory and experiment | 489–504 |
| Scavarda, S. | Control of an electropneumatic actuator: comparison between some linear and non-linear control laws | 387–406 |
| Schoenau, G. J. | Neural networks and hydraulic control—from simple to complex applications | 349–358 |
| Seng, T. L. | Adaptive general regression neural network for modelling of dynamic plants | 275–287 |
| Sesmat, S. | Control of an electropneumatic actuator: comparison between some linear and non-linear control laws | 387–406 |
| Setchi, R. M. | Intelligent product manuals | 65–76 |
| Song, G. | Robust friction compensation for precise and smooth position regulation | 157–161 |
| Sunar, M. | Substructural control design for serial flexible structures using the linear quadratic Gaussian method | 289–300 |
| Sutton, R. P. | Modelling and $H^{\infty}$ control of a single-link flexible manipulator | 85–104 |
| Szyszkowski, W. | Parameter identification and trajectory following of a two-link rigid manipulator | 455–466 |
| Thomasset, D. | Control of an electropneumatic actuator: comparison between some linear and non-linear control laws | 387–406 |
| Thompson, D. F. | Parametric model development and quantitative feedback design for automotive torque converter bypass clutch control | 249–266 |
| Thompson, S. | Adaptive fuzzy logic control of engine idle speed | 145–155 |
| Thornhill, M. | Adaptive fuzzy logic control of engine idle speed | 145–155 |
| Tokhi, M. O. | Geometry-related constraints in the design of active noise control systems | 183–199 |


© IMechE 1999

| | | |
|---|---|---|
| Tso, S. K. | Performance improvement of robot manipulator control using an on-line neural network compensator | 49–60 |
| Ukrainetz, P. R. | Neural networks and hydraulic control—from simple to complex applications | 349–358 |
| Virvalo, T. | Low-order dynamic model for flexible hydraulic cranes | 11–22 |
| Wang, Y. | Robust friction compensation for precise and smooth position regulation | 157–161 |
| Watton, J. | A real-time expert system for the condition monitoring of hydraulic control systems in a hot steel strip finishing mill | 359–374 |
| Watton, J. | A time-encoded signal-processing approach to fault classification of an electrohydraulic pressure control system and its application to a hot steel strip rolling mill | 407–426 |
| Whalley, R. | Hybrid modelling, simulation and torque control of a marine propulsion system | 1–10 |
| Whalley, R. | Mechanical drive control | 301–310 |
| Whalley, R. | Multivariable system regulation with minimum control effort | 505–514 |
| Wilson, D. A. | Modelling and $H^{\infty}$ control of a single-link flexible manipulator | 85–104 |
| Wilson, P. A. | An intelligent guidance and control system for ship obstacle avoidance | 311–320 |
| Wong, C. W. | Modelling and identification of a wire-cable vibration isolator via a cyclic loading test. Part 1: experiments and model development | 163–171 |
| Wong, C. W. | Modelling and identification of a wire-cable vibration isolator via a cyclic loading test. Part 2: identification and response prediction | 173–182 |
| Wright, J. R. | Robust strategies for active vibration control of plate-like structures: theory and experiment | 489–504 |
| Wu, C.-Y. | Non-linear system identification using genetic algorithms | 105–118 |
| Wynne, R. J. | Robust strategies for active vibration control of plate-like structures: theory and experiment | 489–504 |
| Yanada, H. | Frequency-shaped sliding mode control of an electrohydraulic servo-motor | 441–448 |
| Yuan, M. | A methodology to reduce large overshoot in a direct neural control system | 449–453 |
| Yusof, R. | Adaptive general regression neural network for modelling of dynamic plants | 275–287 |
| Zhan, S. | Modelling and identification of a wire-cable vibration isolator via a cyclic loading test. Part 1: experiments and model development | 163–171 |
| Zhan, S. | Modelling and identification of a wire-cable vibration isolator via a cyclic laoding test. Part 2: identification and response prediction | 173–182 |
| Zhang, Q. | Hydraulic actuator control with open-centre electrohydraulic valve using a cerebellar model articulation controller neural network algorithm | 33–48 |




© IMechE 1999